

# UTILITY PATENT APPLICATION TRANSMITTAL

Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 862.C2010

First Named Inventor or Application Identifier

YURIYO ASAMI

Express Mail Label No.

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Fee Transmittal Form  
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification Total Pages **33**
3. ☒ Drawing(s) (35 USC 113) Total Sheets **12**
4. ☒ Oath or Declaration Total Pages **1**
- a. ☒ Newly executed (original or copy)
- b. ☐ Unexecuted for information purposes
- c. ☐ Copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 17 completed)  
[Note Box 5 below]
- i. ☐ **DELETION OF INVENTOR(S)**  
Signed Statement attached deleting  
inventor(s) named in the prior application, see  
37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4c is checked)  
The entire disclosure of the prior application, from which a copy of  
the oath or declaration is supplied under Box 4c, is considered as  
being part of the disclosure of the accompanying application and is  
hereby incorporated by reference therein.

## ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application  
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)
16. ☐ Other: \_\_\_\_\_

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. \_\_\_\_\_

## 18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

05514

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

NAME

Address

City

State

Zip Code

Country

Telephone

Fax



CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
TOTAL CLAIMS (37 CFR 1.16(c))		42-20 =	22	X \$ 18.00 =	\$ 396.00
INDEPENDENT CLAIMS (37 cfr 1.16(b))		8-3 =	5	X \$ 78.00 =	\$ 390.00
MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))				\$ 260.00 =	\$ 0.00
				BASIC FEE (37 CFR 1.16(a))	\$ 690.00
Total of above Calculations =					\$ 1476.00
Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28)					
TOTAL =					\$ 1476.00

19. Small entity status

- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.


20. ☒ A check in the amount of \$ 1476.00 to cover the filing fee is enclosed.

21. ☒ A check in the amount of \$ 40.00 to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☐ Fees required under 37 CFR 1.17
- c. ☐ Fees required under 37 CFR 1.18.

**SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED**

NAME	Lawrence A. Stahl - Reg. No. 30,110
SIGNATURE	
DATE	September 18, 2000

LASlcmv

TITLE OF THE INVENTION  
INFORMATION PROCESSING APPARATUS AND METHOD

FIELD OF THE INVENTION

5           The present invention relates to an information processing apparatus and method for generating printing data as the basis for template data, and a computer-readable memory.

10 BACKGROUND OF THE INVENTION

          In both-sided printing performed by a conventional printer, a system supplies the same printing data as in one-sided printing to the printer. Accordingly, odd-numbered pages in one-sided printing  
15 are printed on the front sides of printing paper sheets, and even-numbered pages are printed on their back sides.

          In the case of a document having a cover, the first page of the text, subsequent to the cover sometimes needs to be started as the first page after  
20 the cover, not from the back side of the cover. In conventional both-sided printing, however, odd-numbered pages in one-sided printing are printed on the front sides of paper sheets, and even-numbered pages are printed on their back sides. Consequently, the first  
25 page following the cover is always the back side of the cover. Also, when an elaborately designed document

such as an album is to be printed, if the total number of pages of the document is an odd number, the back side of the last page becomes white (= solid). This makes the document inappropriate in design.

5

#### SUMMARY OF THE INVENTION

The present invention has been made in consideration of the above problems, and has as its object to provide an information processing system, information processing apparatus and method and computer-readable memory, which can easily realize printing in a print layout desired by a user.

The present invention is characterized by an An information processing method of printing a cover image and a plurality of body images on both sides of a plurality of sheets, comprising: a step of determining one of a first mode for printing a first image of a body on a first side of a second sheet and a second mode for printing the first image on a second side of a first sheet; a generation step of generating an image to be printed on the second side of the first sheet when the first mode is determined; and a printing control step of controlling printing such that when the second mode is determined, the cover image and the body images are printed on a first side of the first sheet and on the second side of the first sheet, respectively,

and image data on both sides of each subsequent sheet,  
and when the first mode is determined, the cover image,  
the image generated in the generation step, and the  
body images are printed on the first side of the first  
5 sheet, on the second side of the first sheet, and on  
both sides of each subsequent sheet starting from the  
first side of the second sheet, respectively.

The another aspect of the invention is, an  
information processing method of printing images on a  
10 plurality of pages, on both sides, comprising: a step  
of printing a first image of the images of the  
plurality of pages on a first side of a first sheet; a  
generation step of automatically generating an image to  
be printed on a second side of the first sheet; and a  
15 step of sequentially printing second and subsequent  
images of the images on the plurality of pages, on both  
sides of each subsequent sheet, starting from a first  
side of a second sheet.

The another aspect of the invention is, an  
20 information processing method of printing a cover image  
and body images on both sides of a plurality of sheets,  
comprising: a step of determining one of a first mode  
for allowing the cover image and the body image to be  
printed on different sides of the same sheet and a  
25 second mode for inhibiting the cover image and the body  
image to be printed on different sides of the same

sheet; and a generation step of generating an image to be inserted between the cover image and the body image when the second mode is determined.

The another aspect of the invention is, an  
5 information processing method of printing images on a plurality of pages on both sides of a plurality of sheets, comprising: a step of acquiring the total number of pages of the image of the plurality of pages; and a generation step of generating an image to be  
10 inserted between an image of the last page and an immediately preceding image thereof of the image of the plurality of pages, on the basis of the acquired total number of pages.

The another aspect of the invention is, an  
15 information processing apparatus for printing a cover image and a plurality of body images on both sides of a plurality of sheets, comprising: means for determining one of a first mode for printing a first image of a body on a first side of a second sheet and a second  
20 mode for printing the first image on a second side of a first sheet; generating means for generating an image to be printed on the second side of the first sheet when the first mode is determined; and printing control means for controlling printing such that when  
25 the second mode is determined, the cover image and the body images are printed on a first side of the first

sheet and on the second side of the first sheet,  
respectively, and both sides of each subsequent sheet,  
and when the first mode is determined, the cover image,  
the image generated by said generating means, and the  
5 body images are printed on the first side of the first  
sheet, on the second side of the first sheet,  
respectively, and on both sides of each subsequent  
sheet starting from the first side of the second sheet.

The another aspect of the invention is, an  
10 information processing apparatus for printing images on  
a plurality of pages on both sides of a plurality of  
sheets, comprising: means for printing a first image  
of the image of the plurality of pages on a first side  
of a first sheet; generating means for automatically  
15 generating an image to be printed on a second side of  
the first sheet; and means for sequentially printing  
second and subsequent images on the plurality of pages  
on both sides of each subsequent sheet starting from a  
first side of a second sheet.

The another aspect of the invention is, an  
20 information processing apparatus for printing a cover  
image and body images on both sides of a plurality of  
sheets, comprising: means for determining one of a  
first mode for allowing the cover image and the body  
25 image to be printed on different sides of the same  
sheet and a second mode for inhibiting the cover image

and the body image to be printed on different sides of the same sheet; and generating means for generating an image to be inserted between the cover image and the body image when the second mode is determined.

5           Another aspect of the invention is, an information processing apparatus for printing images on a plurality of pages, on both sides, comprising: means for acquiring the total number of pages of the images of the plurality of pages; and generating means for  
10   generating an image to be inserted between an image of the last page and an immediately preceding image thereof of the image including the plurality of pages, on the basis of the acquired total number of pages.

Other features and advantages of the present  
15   invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

20

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together  
25   with the description, serve to explain the principles of the invention.



00664279.001000

Fig. 1 is a block diagram showing a configuration of an information processing system to which a both-sided printing means of an embodiment of the present invention is applied;

5        Fig. 2 is a view showing an example of a front cover page template of an album in the embodiment of the present invention;

10       Fig. 3 is a view showing an example of a back cover page template of the album in the embodiment of the present invention;

      Fig. 4 is a view showing an example of a body page of template the album in the embodiment of the present invention;

15       Fig. 5 is a flow chart showing processing executed by the embodiment of the present invention;

      Fig. 6 is a view showing an example of a printing dialogue in the embodiment of the present invention;

20       Fig. 7 is a view showing an output example when "body page = back side of front cover page" of an album in the embodiment of the present invention;

      Fig. 8 is a view showing an output example when "body page = next page of front cover page" of an album in the embodiment of the present invention;

25       Fig. 9 is a view showing an output example when the last page of the body is a front side and "back

cover = the same as body" of an album in the embodiment of the present invention;

Fig. 10 is a view showing an output example when the last page of the body is a front side and "back cover = independent of body" of an album in the embodiment of the present invention;

Fig. 11 is a view showing an output example when the last page of the body is a back side and "back cover = outside" of an album in the embodiment of the present invention; and

Fig. 12 is a view showing an output example when the last page of the body is a back side and "back cover = inside" of an album in the embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will be described below.

An example of an information processing system is disclosed in Japanese Patent Laid-Open No. 10-232946. In this system, a storage device or the like stores a plurality of types of templates (including a both-sided printing template and a one-sided printing template) having predetermined output formats. The system allows a user to select a desired template, fits output data such as a photographic image or character information

to the selected template, and outputs the result. In this embodiment, the formation of an album using such an information processing system will be described.

Fig. 1 is a block diagram showing the configuration of an information processing system to which a both-sided printing function of the embodiment of the present invention is applied.

This information processing system comprises a central processing unit 1, a storage device 2, a keyboard 3, a mouse 4, a display unit 5, and a printing unit 6.

The central processing unit 1 includes a CPU, RAM, ROM, and the like (not shown). On the basis of control programs stored in the ROM or various programs for executing processing explained in the present invention, the CPU controls diverse components of this information processing system. The storage device 2 contains a storage medium such as a hard disk and stores various programs and various data including templates described above. This storage device 2 can also be an external storage device. The display unit 5 is, e.g., a CRT or an LCD and displays diverse information. This display unit 5 also displays GUI (Graphical User Interface) for executing processing explained in the present invention. A user can input various information by this GUI by using the mouse 4 and the keyboard 3. The printing

unit 6 contains a printing engine of a printing system such as an inkjet system or a laser beam system. On the basis of output printing data from the central processing unit, the printing unit 6 prints an image on a printing medium.

An album template utilized in this embodiment includes templates for a cover page and a body page. It is possible to discriminate between these two types of pages by checking page attribute on the template. A plurality of such templates are stored in the storage device 2. When a user inputs an identification code given to each template by using the mouse 4 or the keyboard 3, the central processing unit 1 displays a template corresponding to the identification code on the display unit 5. The user can confirm the design of the template by viewing the displayed contents on the display unit 5 and determine an album template, which he or she desires. In this embodiment, it is assumed that a "cover" page is one page. However, the present invention is not limited to this embodiment, so a "cover" page can include images of a plurality of pages.

One template example will be described below.

Fig. 2 shows a cover (front) page of an album template chosen by a certain user. This cover (front) page is composed of wall paper 201 as a pasteboard, character frame 202 in which a cover title is placed,

and image frame 203 in which a cover image is placed. The user fits a desired original character string and original photograph in character frame 202 and image frame 203, respectively, to form output data. Fig. 3 shows a cover (back) page of the same template. This cover (back) page is composed of wall paper 301 as a pasteboard and character frame 302 in which a back cover comment is placed. The user fits a desired original character string in character frame 302 to form output data.

Fig. 4 shows a body page of the same template. This body page is composed of wall paper 401 as a pasteboard and image frame 402 in which a photographic image is placed. The user fits a desired original photograph in image frame 402 to form output data. The number of this body pages is not limited to one; a plurality of body pages sometimes continue depending on the number of original photographs.

Processing executed in this embodiment will be described next with reference to Fig. 5.

Fig. 5 is a flow chart showing processing executed by the embodiment of the present invention.

Processing when both-sided printing is to be performed by the output data of the album template formed as above will be explained.

Before printing the album template output data completed as described above, the central processing unit 1 displays a printing dialogue as shown in Fig. 6 on the display unit 5. In this printing dialogue, a user can designate the type and size of printing sheet, the number of copies, the page range, and the print quality. The user can also determine "one side" or "both side" printing. When both side is chosen, some processes unique to both-sided printing can be performed. In this embodiment, two items start position of body pages (Beginning Body) 700 and display position of back cover (Back Cover) 701 can be set for the processes.

The start position of body pages can be set to back side of cover ("Back Page" button 700a) or next sheet of cover ("Next Sheet" button 700b). Fig. 7 shows an output example when "Back Page" button 700a is chosen. Fig. 8 shows an output example when "Next Sheet" button 700b is chosen. In Figs. 7 and 8, the top right image 801a is an image of the front page of the first sheet; the bottom left image 801b is an image of the back of the first sheet; and the lower right image 802 is the front page of the second sheet. In particular, Fig. 8 shows that a unique insertion page is necessary as the back side page 801b of the cover 801a.

The display position of back cover can be set to the same sheet as body ("General" button 701a) or independent sheet of body ("Independent" button 701b). Back cover pairs with front cover and should come to the outermost side when a book is bound. Hence, back cover must be printed on the back side of a sheet.

In Figs. 9 through 12, the bottom left image is an image of the back page of the last sheet; the top right image (in Fig. 10, the middle right image) is an image of the front page of the last sheet; and the top left image (in Fig. 10, the middle left image) is the back page of the second last sheet. In Fig. 10, the top right image is an image of the front page of the second last sheet; the top left image is an image of the back page of the third last sheet.

As shown in Fig. 12, if back cover1202a is printed subsequently to body although the last body page 1201 is the back side of an output sheet, the outermost side 1202b of the bound book becomes a white page (= solid) having nothing printed on it and hence does not serve as back cover any longer. Therefore, as shown in Fig. 11, if the last body page 1101 is the back side of an output sheet, a separate insertion page 1102a corresponding to the front side of back cover1102b is always necessary.

On the other hand, when the last body page is the front side of an output sheet, if "General" button 701a is selected, back cover is printed, as shown in Fig. 9, on the back side 901b of the last body page 901a, subsequently to body (back cover = the same sheet as body), or if "Independent" button 701b is selected, a sheet, different from a sheet which the last body page 901a is printed, is specially prepared for printing back cover 901b, as shown in Fig. 10.

Assume that in the printing dialogue shown in Fig. 6, the user sets "printing sides = both sides", "Beginning Body = Next Sheet", and "Back Cover = Independent", and presses a "Print" button 702 to start printing. Processing in this case will be described below with reference to the flow chart in Fig. 5.

Upon receiving this printing start instruction, the central processing unit 1 reads out the settings of the template of a document to be printed and stores the readout settings in the storage device 2 (step S201). Since the template used is as shown in Figs. 2 and 3, the storage device 2 stores "front cover = present" and "back cover = present".

The central processing unit 1 then reads out printing format information set in the printing dialogue in Fig. 6 and stores the readout information in the storage device 2 (step S202). Since the set



values in this example are as shown in Fig. 6, the storage device 2 stores "Beginning Body = Next Sheet" and "Back Cover = Independent".

Subsequently, the central processing unit 1 reads  
5 out the information of "the presence/absence of front cover" stored in step S201 from the storage device 2 and checks the information (step S203). If the central processing unit 1 determines that "front cover = absent", the flow advances to step S206. If the  
10 central processing unit 1 determines that "front cover = present", the flow advances to step S204.

Since the set value in this example is "front cover = present", the central processing unit 1 reads out the information of " Beginning Body " stored in  
15 step S202 from the storage device 2 and checks the information (step S204). If the central processing unit 1 determines that "Beginning Body = Back Page", the flow advances to step S206. If the central processing unit 1 determines that "Beginning Body =  
20 Next Sheet", the flow advances to step S205.

Since the set value in this example is "Beginning Body = Next Sheet", the central processing unit 1 forms a new page by copying the page of front cover shown in Fig. 2. The central processing unit 1 then removes  
25 image frame and character frame as components of this new page and leaves only wall paper behind, thereby, as

shown in Fig.8, forming a page 801b (having only a  
pasteboard ) to be inserted into a position  
corresponding to the back side of front cover. The  
central processing unit 1 adds this page between front  
5 cover and the first page of body and stores the data in  
the storage device 2 (step S205).

Subsequently, the central processing unit 1 reads  
out the information of "the presence/absence of back  
cover" stored in step S201 from the storage device 2  
10 and checks the information (step S206). If the central  
processing unit 1 determines that "back cover =  
present", the flow advances to step S209. If the  
central processing unit 1 determines that "back cover =  
absent", the flow advances to step S207.

15 In step S207, the central processing unit 1  
counts the total number of output pages and checks  
whether the count is an even number or odd number. If  
the total number of output pages is an even number, the  
last page of the body is printed on the back side of a  
20 sheet, so printing can be started with the output data  
formed up. Therefore, the flow advances to step S214.  
If the total number of output pages is an odd number,  
the last page of the body is printed on the front side  
of a sheet, so printing must be started after a page  
25 equivalent to a pasteboard of the album is added as the  
last page. Accordingly, the central processing unit 1

forms a new page by copying the page of body shown in Fig. 4, removes image frame as a component of this new page and leaves only wall paper behind to form an insertion page (having only a pasteboard), adds this  
5 insertion page after the last page, and stores the data in the storage device 2 (step S208).

Since it is determined that the set value is "back cover = present" in step S206, the flow advances to step S209. In step S209, the central processing  
10 unit 1 counts the total number of output pages except for the back cover (= the number of output pages - 1) and checks whether the count is an even number or odd number. If the total number of output pages, except the back cover, is an even number, the last page of the  
15 body 1101 is printed on the back side of a sheet as shown in Fig. 11. Therefore, printing must be started after a page 1102a corresponding to the front side of back cover 1102b is added as a page before back cover 1102b. Hence, the central processing unit 1 forms a  
20 new page by copying the page of back cover 1102b, removes character frame as a component of this new page to form an insertion page with only wall paper, adds this insertion page 1102a immediately before the back cover page 1102b, and stores the data in the storage  
25 device 2 (step S210).



insertion page 1001b immediately before the back cover page 901b, and stores the data in the storage device 2 (step S213).

In this manner, the central processing unit 1  
5 appropriately adds a page to obtain the desired output form in accordance with the presence/absence of a cover, the position of a body beginning page, the position of a back cover, and the number of pages to be output. The central processing unit 1 reads out this output  
10 data from the storage device 2 and transfers the data to the printing unit 6 (step S214).

In this embodiment as described above, in accordance with various settings corresponding to both-sided printing, output data having set contents is  
15 generated and outputted to the printing unit 6. Accordingly, the printing unit 6 can output a printing result having an optimum layout, desired by a user, only by directly printing the received output data. (Other embodiments)

20 The drawings used in the explanation of the above embodiment are merely examples. For instance, the design of the printing dialogue shown in Fig. 6 can be changed. Also, the setting items of the printing layout for both-sided printing can be changed to  
25 contents other than those shown in Fig. 6, or some other items can be added. For example, in Fig. 6 it is

possible to add an item for selecting a method of forming an additional page to be inserted in, e.g., the back side of a front cover.

In addition, in the above embodiment a GUI allows  
5 a user to set setting items of the print layout for both-sided printing by using the print dialogue shown in Fig. 6. However, it is also possible to include these setting items in the form of registry settings as system information and permit the system to  
10 automatically set the setting items of the printing layout in accordance with a service form or a template.

Furthermore, the present invention can also be extended such that page data used only in both-sided printing is formed in a template. As an example, "back  
15 side page of front cover" and "front side page of back cover" shown in Figs. 2 and 3, respectively, can be formed in template data as pages to be used only in both-sided printing. These pages are not used in one-sided printing. Even in both-sided printing, if a  
20 layout desired by a user is "body beginning position = back side of front page", "back side page of front cover" is not used. Also, if the last page of the body is the front side and "back cover = the same as body", "front side page of back cover" is not used.  
25 Furthermore, it is possible to prepare one-sided printing template data and both-sided printing template

data and generate printing data by using necessary template data and deleting unnecessary template data in accordance with printing designation (one-sided printing or both-sided printing).

5           The present invention can be applied to a system constituted by a plurality of devices (e.g., a host computer, interface, reader, and printer) or to an apparatus (e.g., a copying machine or facsimile) comprising a single device.

10           Further, the object of the present invention can also be achieved by providing a storage medium storing program codes of software for performing the aforesaid functions according to the embodiments to a system or an apparatus, reading the program codes with a computer  
15 (or a CPU or MPU) of the system or apparatus from the storage medium, and then executing the program.

          In this case, the program codes read from the storage medium realize the functions according to the embodiments, and the storage medium storing the program  
20 codes constitutes the invention.

          As the storage medium for providing the program codes, it is possible to use, e.g., a floppy disk, hard disk, optical disk, magnetooptical disk, CD-ROM, CD-R, magnetic tape, nonvolatile memory card, and ROM.

25           Furthermore, besides aforesaid functions according to the above embodiments are realized by

executing the program codes which are read by a computer, the present invention includes a case where an OS (Operating System) or the like running on the computer performs a part or the whole of actual  
5 processing in accordance with designations by the program codes and realizes functions according to the above embodiments.

Furthermore, the present invention also includes a case where, after the program codes read from the  
10 storage medium are written in a memory of a function extension board which is inserted into a computer or of a function extension unit which is connected to a computer, a CPU or the like of the function extension board or unit performs a part or the whole of actual  
15 processing in accordance with designations by the program codes and realizes functions of the above embodiments.

When the present invention is applied to the storage medium, this storage medium stores program  
20 codes corresponding to the flow chart shown in Fig. 5 explained earlier.

As has been described above, the present invention can provide an information processing apparatus and method and computer-readable memory  
25 capable of easily realizing printing in a printing layout desired by a user.



The present invention is not limited to the above embodiments and various changes and modifications can be made within the spirit and scope of the present invention. Therefore, to apprise the public of the scope of the present invention, the following claims

5 are made.

WHAT IS CLAIMED IS

1. An information processing method of printing a cover image and a plurality of body images on both sides of a plurality of sheets, comprising:

5 a step of determining one of a first mode for printing a first image of a body on a first side of a second sheet and a second mode for printing the first image on a second side of a first sheet;

10 a generation step of generating an image to be printed on the second side of the first sheet when the first mode is determined; and

15 a printing control step of controlling printing such that when the second mode is determined, the cover image and the body images are printed on a first side of the first sheet and on the second side of the first sheet, respectively, and image data on both sides of each subsequent sheet, and

20 when the first mode is determined, the cover image, the image generated in the generation step, and the body images are printed on the first side of the first sheet, on the second side of the first sheet, and on both sides of each subsequent sheet starting from the first side of the second sheet, respectively.

2. The method according to claim 1, further comprising a step of generating the body images by laying out original images as the basis for a template.

3. The method according to claim 2, wherein the template contains a background image.

4. The method according to claim 2, wherein the generation step comprises using a background image in the template.

5. An information processing method of printing images on a plurality of pages, on both sides, comprising:

a step of printing a first image of the images of the plurality of pages on a first side of a first sheet;

a generation step of automatically generating an image to be printed on a second side of the first sheet; and

a step of sequentially printing second and subsequent images of the images on the plurality of pages, on both sides of each subsequent sheet, starting from a first side of a second sheet.

6. The method according to claim 5, further comprising a generation step of generating the image by laying out an original image as the basis for a template.

7. The method according to claim 6, wherein the template contains a background image.

8. The method according to claim 6, wherein the generation step of generating the image by laying out

an original image comprises using a background image in the template.

9. An information processing method of printing a cover image and body images on both sides of a

5 plurality of sheets, comprising:

a step of determining one of a first mode for allowing the cover image and the body image to be printed on different sides of the same sheet and a second mode for inhibiting the cover image and the body  
10 image to be printed on different sides of the same sheet; and

a generation step of generating an image to be inserted between the cover image and the body image when the second mode is determined.

15 10. The method according to claim 9, further comprising a generation step of generating the body image by laying out an original image as the basis for a template.

11. The method according to claim 10, wherein the  
20 template contains a background image.

12. The method according to claim 10, wherein the generation step of generating the body image by laying out an original image comprises a step of using a background image in the template.

13. An information processing method of printing images on a plurality of pages on both sides of a plurality of sheets, comprising:

5 a step of acquiring the total number of pages of the image of the plurality of pages; and  
a generation step of generating an image to be inserted between an image of the last page and an immediately preceding image thereof of the image of the plurality of pages, on the basis of the acquired total  
10 number of pages.

14. The method according to claim 13, further comprising the determination step of determining whether the total number of pages is an even number or whether the total number of pages is an odd number,

15 wherein the generation step is based on the determination result in the determination step.

15. The method according to claim 13, further comprising a generation step of generating the image by laying out an original image as the basis for a  
20 template.

16. The method according to claim 15, wherein the template contains a background image.

17. The method according to claim 15, wherein the generation step of generating the image by laying out  
25 an original image comprises a step of using a background image as the template.

18. An information processing apparatus for printing a cover image and a plurality of body images on both sides of a plurality of sheets, comprising:

means for determining one of a first mode for  
5 printing a first image of a body on a first side of a second sheet and a second mode for printing the first image on a second side of a first sheet;

generating means for generating an image to be printed on the second side of the first sheet when the  
10 first mode is determined; and

printing control means for controlling printing such that when the second mode is determined, the cover image and the body images are printed on a first side of the first sheet and on the second side of the first  
15 sheet, respectively, and both sides of each subsequent sheet, and

when the first mode is determined, the cover image, the image generated by said generating means, and the body images are printed on the first side of  
20 the first sheet, on the second side of the first sheet, respectively, and on both sides of each subsequent sheet starting from the first side of the second sheet.

19. The apparatus according to claim 18, further comprising means for generating the body images by  
25 laying out original images as the basis for a template.

00564379 0013000

20. The apparatus according to claim 19, wherein the template contains a background image.

21. The apparatus according to claim 19, wherein said generating means uses a background image in the  
5 template.

22. An information processing apparatus for printing images on a plurality of pages on both sides of a plurality of sheets, comprising:

means for printing a first image of the image of  
10 the plurality of pages on a first side of a first sheet;

generating means for automatically generating an image to be printed on a second side of the first sheet; and

15 means for sequentially printing second and subsequent images on the plurality of pages on both sides of each subsequent sheet starting from a first side of a second sheet.

23. The apparatus according to claim 22, further  
20 comprising generating means for generating the image by laying out an original image as the basis for a template.

24. The apparatus according to claim 23, wherein the template contains a background image.

25. The apparatus according to claim 23, wherein said generating means for generating the image by laying out

an original image uses a background image in the template.

26. An information processing apparatus for printing a cover image and body images on both sides of a plurality of sheets, comprising:

means for determining one of a first mode for allowing the cover image and the body image to be printed on different sides of the same sheet and a second mode for inhibiting the cover image and the body image to be printed on different sides of the same sheet; and

generating means for generating an image to be inserted between the cover image and the body image when the second mode is determined.

27. The apparatus according to claim 26, further comprising generating means for generating the body image by laying out an original image as the basis for a template.

28. The apparatus according to claim 27, wherein the template contains a background image.

29. The apparatus according to claim 27, wherein said generating means for generating the image by laying out an original image uses a background image in the template.



30. An information processing apparatus for printing images on a plurality of pages, on both sides, comprising:

means for acquiring the total number of pages of the images of the plurality of pages; and

generating means for generating an image to be inserted between an image of the last page and an immediately preceding image thereof of the image including the plurality of pages, on the basis of the acquired total number of pages.

31. The apparatus according to claim 30, further comprising a determining means for determining whether the total number of pages is an even number or odd number,

wherein said generating means is based on the determination result by said determining means.

32. The apparatus according to claim 30, further comprising generating means for generating the image by laying out an original image as the basis for a template.

33. The apparatus according to claim 32, wherein the template contains a background image.


34. The apparatus according to claim 32, wherein said generating means for generating the image by laying out an original image uses a background image in the template.

35. A storage medium storing a computer program for  
executing the method according to claim 1.
36. A storage medium storing a computer program for  
executing the method according to claim 5.
- 5 37. A storage medium storing a computer program for  
executing the method according to claim 9.
38. A storage medium storing a computer program for  
executing the method according to claim 13.
39. A computer program product for executing the  
10 method according to claim 1.
40. A computer program product for executing the  
method according to claim 5.
41. A computer program product for executing the  
method according to claim 9.
- 15 42. A computer program product for executing the  
method according to claim 13.


# ABSTRACT OF THE DISCLOSURE

An information processing apparatus capable of setting the start position of body pages to back side of cover or next sheet of cover. When the body pages  
5 are set to start from the back side of the cover, the cover is printed on the first side of the first sheet, the first page of the body is printed on the second side of the first sheet, and the second and subsequent pages of the body are printed on both sides of the  
10 second and subsequent sheets. When the body pages are set to start from a sheet different from the cover, the cover is printed on the first side of the first sheet, only a background image of the cover is printed on the second side of the first sheet, which is the back side  
15 of the cover, and the body pages are printed on both sides of the second and subsequent sheets.


FIG. 1



**FIG. 2**



**FIG. 3**











FIG. 6

Print

---

 Album

---

Paper: A4 Roll


Size: 1260X0w  
1260X0h  
mm

☒ mm  
☐ inch

---

Number of Copies: 1

EX: page 1 and 3 = 1-3  
page 1 to page 3 = 1-3

Page Range: ALL Specified

Print Quality: Standard Fine

Printing sides: One Side Both Side

700a 700b


700 Beginning Body: (For Front Cover)

701 Back Cover: (Relate with Body)

Back Page	Next Sheet
General	Independent

701a 701b

702

 Print

Cancel

FIG. 7






FIG. 8



**FIG. 9**



10/12  
**FIG. 10**







FIG. 12



COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION

(Page 1)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

INFORMATION PROCESSING APPARATUS AND METHOD

the specification of which [X] is attached hereto. [ ] was filed on \_\_\_\_\_

as United States Application No. or PCT International Application No. \_\_\_\_\_  
and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

<u>Country</u>	<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>(Yes/No)</u> <u>Priority Claimed</u>
JAPAN	11-279383	30/09/1999	Yes

I hereby appoint the practitioners associated with the firm and customer number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

**FITZPATRICK, CELLA, HARPER & SCINTO**  
**Customer Number: 05514**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor Yuriyo ASAMI  
Inventor's signature Yuriyo Asami  
Date September 11, 2006 Citizen/Subject of Japan  
Residence 20-21, Natsumi 6-chome, Funabashi-shi,  
Chiba-ken, Japan  
Post Office Address c/o CANON KABUSHIKI KAISHA,  
30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo, Japan  
F511/A601948/ald